



Rail Type	Lmax (mm)	F0 (mm)	F (mm)	S1	Cr (mm)	Br (mm)	T	Hc (mm)
SBR10	4000	20	100	4,5	22	30	4	36,3
SBR12	4000	20	100	4,5	22	30	4	39,4
SBR16	4000	20	150	5,5	30	40	5	45
SBR20	4000	20	150	5,5	30	45	5	50
SBR25	4000	25	200	6,6	35	55	6	60
SBR35	4000	25	200	9	45	65	8	80

Block Type	SHD (mm)	L (mm)	B (mm)	C (mm)	S	W (mm)	Dyn C (N)	Stat C0 (N)
SBRB10	10	32	25	20	M5	36	372	549
SBRB12	12	39	28	26	M5	40	510	784
SBRB16	16	45	32	30	M5	45	774	1180
SBRB20	20	50	35	35	M6	49	882	1370
SBRB25	25	65	40	40	M6	60	980	1570
SBRB35	35	80	55	55	M8	80	1670	3140

Block Type	SHD (mm)	L (mm)	B (mm)	C (mm)	S	W (mm)	Dyn C (N)	Stat C0 (N)
SBRB10L	10	68	25	46	M5	36	774	1020
SBRB12L	12	75	28	50	M5	40	1020	1548
SBRB16L	16	85	32	60	M5	45	1548	2360
SBRB20L	20	96	35	70	M6	49	1760	2740
SBRB25L	25	130	40	100	M6	60	1960	3140
SBRB35L	35	155	55	120	M8	80	3340	6280

MATERIAL	STOCK DIM	WEIGHT (g)	SURFACE TREAT.	NOTES
----------	-----------	------------	----------------	-------

CNC PRISLUSENSTVO. SK This documentation is the intellectual property of CNC PRISLUSENSTVO SK.
 Feel free to share it and visit our e-shop www.cncprislusenstvo.sk

	NAME	SIGN	DATE	Dimmensions are in mm Tolerances: ISO 8015 Accuracy: ISO 2768 mK
DRAWN				
CHECKED				
APPROVED				
PRODUCT NAME:				
DWG NAME:				

SCALE	4:5	SIZE	A3
DATE	2/27/2018		
DWG NO.			
SBR-ASS			
REVISION :			