		7 6 5	7 6 5 4	7 6 5 4 3	7 6 5 4 3 2
el h [mm] _UU 18,0 _UU 21,0 _UU 28,0	31,0 85,0 62,0 34,0 96,0 68,0	31,0 85,0 62,0 26,0 8,0 50,0 34,0 96,0 68,0 31,0 10,0 54,0	31,0 85,0 62,0 26,0 8,0 50,0 60,0 M5 34,0 96,0 68,0 31,0 10,0 54,0 70,0 M6	31,0 85,0 62,0 26,0 8,0 50,0 60,0 M5 392 490 34,0 96,0 68,0 31,0 10,0 54,0 70,0 M6 784 1176	31,0 85,0 62,0 26,0 8,0 50,0 60,0 M5 392 490 360 34,0 96,0 68,0 31,0 10,0 54,0 70,0 M6 784 1176 600
28,0 33,5	41,0 130,0 82,0	41,0 130,0 82,0 41,0 12,0 65,0	41,0 130,0 82,0 41,0 12,0 65,0 100,0 M8	41,0 130,0 82,0 41,0 12,0 65,0 100,0 M8 1568 2352	41,0 130,0 82,0 41,0 12,0 65,0 100,0 M8 1568 2352 1200
		D±0,02			
	1±0,02				
		B±0,2	B±0.2	B±0,2	B±0.2
				T T T T T T T T T T T T T T T T T T T	MATERIAL STOCK DIM WEIGHT (g) SURFACE TREAT.
		L C±0,2			This documentation is the intellectual property of CNC P PRISLUSENSTVO. SK Feel free to share it and visit our e-shop www.cncprisluse
	Ċ			DRAWN DATE	NAME SIGN DATE DRAWN DRAWN